



TruVision IP Keypad (TVK-800)



Overview

Efficiently control the monitor outputs of multiple recorders and decoders with the TruVision® IP Keypad (TVK-800). An IP keypad designed to be used with the line of TruVision NVRs and DVRs.

Providing a breadth of functionality, the keypad can be controlled using the touch screen display, fully functional buttons, embedded touch pen, or 4-axis joystick.

The touch screen display enables you to view live or recorded camera footage, configure recorder settings or manage different views.

The joystick allows you to smoothly control PTZ movement and navigate between menus.

Relieving the requirement for a separate power supply, the TVK-800 keypad works on a 12V DC as well as PoE-af.

Standard features

- Control a variety of NVRs, DVRs and decoders with one keypad
- Perform PTZ control
- Display IP cameras on embedded display
- Control recorder OSD
- Control monitor outputs of recorders
- · Setting and calling presets and shadow tours
- 7-inch touch screen display
- 4-axis joystick
- Numeric and functional buttons
- PoE-af support
- Embedded touch pen

TruVision IP Keypad (TVK-800)

Interlogix National Sales Enquiries 1300 361 479 271-273 Wellington Road Mulgrave Vic 3170 T +61 3 9239 1200 F +61 3 9239 1298

Specifications

| Opcomoditorio | |
|-----------------------------|---------------------------------------------------|
| TFT LCD Options | |
| Display | 7-inch TFT LCD monitor with touch panel |
| Embedded display resolution | 800 x 480 |
| Operations | |
| Joystick | 4-axis navigation |
| Buttons | Numerical and functional |
| Touch pen | Embedded in keypad |
| Audio input/output | |
| Line in | 1-ch, 3.5 mm connector (2.0 Vp-p, 1 k Ohm) |
| Audio out | 1-ch, 3.5 mm connector (Linear, 600 Ohm) |
| External interface | |
| Network interface | 1 x 100M/1000M Ethernet interface |
| RS-232 interface | 1 x RS-232 interface |
| RS-485 interface | 1 x RS-485 interface |
| USB interface | 1 x USB 2.0 (for data storage and device upgrade) |
| General | |
| Power supply | 12V DC, PoE |
| Power consumption | less than 15W |
| Operating temperature | -10°C ~ +50°C |
| Operating humidity | 10% ~ 90% |
| Dimensions (W x D x H) | 193 x 435 x 110 mm |
| Weight | 2040 g |
| Supported products | |
| Devices | TVE-DEC10, TVN20/21/21P/50, TVR11/41/42 |
| | |

Front Panel Overview



Back Panel Overview



Ordering information

TruVision IP Keypad, 7-inch LCD touch screen

Specifications subject to change without notice.

Copyright © 2014 UTC Fire & Security Australia Pty Ltd. All rights reserved.





